

# Sieve Shaker EFL 300

### **General Information**

The new Sieve Shaker EFL 300 combines the best features of the EFL2 whilst incorporating modern sieve shaker technology.

The EFL 300 is still extremely robust but at the same time lightweight and more powerful than its predecessor - heavier and larger samples can now be sieved.

The sieve shaker EFL 300 is very versatile. Amplitude setting is now standard. The heavy electric motor is replaced by the electromagnetic system found in all modern sieve shakers. Its lighter form means that it can be either floor standing or even bench mounted making it suitable for both, laboratory and industrial environments. Sieving parameters are set by the remote control unit. Its functions are logical and very simple to operate.



## **Advantages**

- New electromagnetic drive
- · Adjustable amplitude
- · Floor or table mounted
- · Suitable for wet or dry sieving
- Digital controls for easy and reliable operation via external interface
- Economical

### **Specifications**

 $\begin{array}{ll} \text{Range} & 20 \ \mu\text{m} - 40 \ \text{mm} \\ \text{Drive / sieving motion} & \text{electromagnetic 3D} \end{array}$ 

Max. batch / feed capacity 6 kg
Max. number of sieves 6 / 12
Max. mass of sieve stack 10 kg

Amplitude 0 - 2 mm digital setting in 10 steps Time display digital, 00:10 - 99:50 min (external

unit)

Suitable for dry sieving yes Suitable for wet sieving yes

Sieve diameter 100 mm / 150 mm / 200 mm 250

mm / 300 mm / 315 mm / 3" / 8" / 12"

Max. height of sieve stack 450 mm

Clamping device quick-release clamping system

included

Model floor or benchtop

Protection code IP 54

Electrical supply different voltages available

Power connection 1-Phase

W x H x D 427 mm x 240 mm

Net weight ~ 45 kg



# Sieve Shaker EFL 300

Standards CE

## **Order Data**

## EFL 300 Sieve Shaker

#### EFL 300 Sieve Shaker

for up to 6 full height 300 mm (12") diameter sieves (to be ordered separately), including quick-release clamping system

EFL300/23050	EFL 300, 230 V, 50 Hz
EFL300/23060	EFL 300, 230 V, 60 Hz
EFL300/10050	EFL 300, 100 V, 50 Hz
EFL300/10060	EFL 300, 100 V, 60 Hz
EFL300/11050	EFL 300, 110 V, 50 Hz
EFL300/11060	EFL 300, 110 V, 60 Hz

Sieves and accessories (receiver, lid, etc.)

# **Wet Sieving Kit**

ZMWSK-EFL300	ø 300 mm, for EFL 300
ZMWSK-EFL300/12	ø 12", for EFL 300
ZMWSK-EFL300/200	ø 200 mm, for EFL 300
ZMWSK-EFL300/8	ø 8", for EFL 300