

Sieve Shaker OCTAGON 200CL

General Information

The new Octagon 200CL for precise, reproducible and error-free sieving processes competes with the most advanced sieve shakers in the world.

Several unique features have been developed specifically for this sieve shaker, including the 'Closed Loop' amplitude control for ultimate reproducibility.

The Octagon 200CL is designed to work with Endecotts' SieveWare, the new software for easy evaluation and documentation of the sieving process.

Advantages

- 'Closed Loop' total amplitude control ensures reproducible sieving
- · Digital controls for easy and reliable operation
- Easy-to-use sieve clamping system
- · Accepts up to 8 full height 200 mm (8") diameter sieves
- Suitable for dry and wet sieving
- 3D sieving motion allows for high separation efficiency and non blinding sieving action
- Full compatibility with new SieveWare evaluation and control software via RS232 Port (printed or digital protocols)
- Voltage-independent
- No mechanical moving parts
- Compact & portable

Specifications

Range 20 μm to 125 mm Drive / sieving motion electromagnetic 3D

Max. batch / feed capacity 3 kg

Max. number of sieves 8 full height / 16 half height (200 mm

sieves)

Amplitude 0 - 3 mm digital setting in 0.1 mm

steps "Closed Loop" amplitude

control

Speed $3,000 \, \mathrm{min^{-1}} \, \mathrm{at} \, 50 \, \mathrm{Hz}$ Time display digital, $00:10 - 99:50 \, \mathrm{min}$

Interval operation yes (two modes)

Suitable for dry sieving yes Suitable for wet sieving yes

Serial interface yes (RS232)
Sieve diameter 100 / 200 mm 8"
Max. height of sieve stack up to 450 mm

Clamping device quick-release clamping system

(included)

Model benchtop





Sieve Shaker OCTAGON 200CL

Protection code IP 54

Electrical supply 100-240V 50/60Hz

Power connection 1 - Phase

W x H x D 418 x 232 x 435 mm

Net weight ~35 kg Standards CE

Order Data

Octagon 200CL Sieve Shaker

Octagon 200CL Sieve Shaker

for up to 8 full height 200 mm (8") diameter sieves (to be ordered separately) including quick-release clamping system

OCT200CL/100-240 V, 50/60 Hz

Sieves and accessories (receiver, lid, etc.)

Wet Sieving Kit

ZMWSK-OCT200 ø 200 mm, for Octagon 200 ZMWSK-OCT200/8 ø 8", for Octagon 200